



Eaton Aeroquip GH681 Series Rubber Hydraulic Braided Hose

GH681-4R250

Dimensions:

- **Height:** .25 IN
- **Length:** 250 FT
- **Width:** .25 IN

Weight:35 LB

Warranties:

Specifications:

- **Application:** Compact construction equipment, Agricultural equipment, Aerial lift equipment, and Other industrial applications needing 1SC pressures
- **Construction:** 1 Ply Braid
- **Tube Material:** Synthetic Rubber
- **Reinforcement Material:** Wire
- **Color:** Black
- **Lay Line Style:** Ink Transfer
- **Conductivity:** Conductive
- **Dash Size:** -4
- **Inside Diameter:** .25 IN
- **Outside Diameter:** .53 IN
- **Working Pressure:** 3700 Psi
- **Burst Pressure:** 14800 Psi
- **Minimum Working Temperature:** -50.8 F
- **Maximum Working Temperature:** 258.8 F
- **Minimum Bend Radius:** 1.97 IN
- **Package Form:** Reel
- **Qualified Hose Fittings:** TTC
- **Abrasion Resistance:** Standard
- **Impulse Cycle Life:** 400000 B7

Supporting documents:

- [Eaton Aeroquip Master Catalog](#)
- [Fluid Compatibility](#)

- [Hydraulic Warranty](#)

Certifications:

- ABS
- EN853 1SN
- EN853 1ST
- SAE 100R17
- SAE 100R1AT
- EN857 1SC

Product compliance:

- DNV
- MSHA Approved
- USCG