Witches Hat Strainers

Features:

- · used with female cam and groove couplings
- pre-attached Buna-N gasket

| Size | 304 Stainless Steel | |
|------|---------------------|---|
| 5120 | Part # | |
| 3" | WH300-A | |
| 4" | WH400-A | |
| • | | 5 |
| | | Õ |
| _ | | |
| | | Φ |

Gaskets for Witches Hat Strainers

| Size | Buna-N Gasket Part # | |
|------|-------------------------|--|
| 3" | WH300-G | |
| 4" | WH400-G | |

Disk Strainers

Feature:

· threads into bottom of female NPT fitting to protect equipment from large contaminants

| Size | Hole Size | 6061T6 Aluminum Part # | 304 Investment Cast Stainless Steel Part # |
|------|--------------|---------------------------|--|
| 2" | 1/4" | SDA200 | SDS200 |
| 3" | 1/4" | SDA300 | SDS300 |
| 4" | 1/4" | SDA400 | SDS400 |



Pull Ring Safety Clips for Boss-Lock™

| Coupler | Carbon Steel | 316 Stainless Steel | |
|------------------------------------|--------------|---------------------|--|
| Size | Part # | Part # | |
| ³ ⁄ ₄ " - 1" | | 100PRSCSS | |
| 1¹⁄ ₄ " - 2¹⁄₂" | 200PRSCCS | 200PRSCSS | |
| 3" and 4" | 300PRSCCS | 300PRSCSS | |

Pull Rings

| 304 Stainless Steel | |
|---------------------|--|
| Part # | |
| R200SS | |

Sash Chain with Pull Rings

Feature:

• brass chain, plated steel pull ring

| Length | Part # | |
|-------------|--------------|--|
| 4½" 6½" | J125 J150 | |
| 8½" 12¾" | J300 J500 | |