

WS-Series Hydraulic Couplings

Application:

- used extensively in oil field and off shore oil rig applications

Features:

- interchanges with Snap-Tite 75 series
- Nitrile (Buna-N) seals standard, providing a temperature range of **-40°F to 250°F (-40°C to 121°C)**
- Contact Dixon® for pressure ratings and other technical information.

High Pressure Wingstyle Female Threaded Couplers

steel



316 stainless

| Body Size | Threads | Steel Part # | 316 Stainless Steel Part # |
|-----------|------------------|-----------------|----------------------------|
| ¾" | ½" - 14 NPTF | 6WSF4 | --- |
| | ¾" - 14 NPTF | 6WSF6 | 6WSF6-SS |
| | ¾" - 14 BSPP | 6WSBF6 | 6WSBF6-SS |
| | 1-1/16" - 12 ORB | 6WSOF6 | --- |
| 1" | 1" - 11½ NPTF | 8WSF8 | 8WSF8-SS |
| | 1" - 11 BSPP | 8WSBF8 | 8WSBF8-SS |
| | 1-5/16" - 12 ORB | 8WSOF8 | --- |
| 1¼" | 1¼" - 11½ NPTF | 10WSF10 | 10WSF10-SS |
| | 1¼" - 11 BSPP | 10WSBF10 | 10WSBF10-SS |
| | 1⅝" - 12 ORB | 10WSOF10 | --- |
| 1½" | 1½" - 11½ NPTF | 12WSF12 | 12WSF12-SS |
| | 1½" - 11 BSPP | 12WSBF12 | 12WSBF12-SS |
| | 1⅞" - 12 ORB | 12WSOF12 | --- |
| 2" | 2" - 11½ NPTF | 16WSF16 | 16WSF16-SS |
| | 2" - 11 BSPP | 16WSBF16 | 16WSBF16-SS |
| | 2½" - 12 ORB | 16WSOF16 | --- |

High Pressure Wingstyle Female Threaded Plugs

steel



316 stainless

| Body Size | Threads | Steel Part # | 316 Stainless Steel Part # |
|-----------|------------------|-----------------|----------------------------|
| ¾" | ½" - 14 NPTF | WS6F4 | --- |
| | ¾" - 14 NPTF | WS6F6 | WS6F6-SS |
| | ¾" - 14 BSPP | WS6BF6 | WS6BF6-SS |
| | 1-1/16" - 12 ORB | WS6OF6 | --- |
| 1" | 1" - 11½ NPTF | WS8F8 | WS8F8-SS |
| | 1" - 11 BSPP | WS8BF8 | WS8BF8-SS |
| | 1-5/16" - 12 ORB | WS8OF8 | --- |
| 1¼" | 1¼" - 11½ NPTF | WS10F10 | WS10F10-SS |
| | 1¼" - 11 BSPP | WS10BF10 | WS10BF10-SS |
| | 1⅝" - 12 ORB | WS10OF10 | --- |
| 1½" | 1½" - 11½ NPTF | WS12F12 | WS12F12-SS |
| | 1½" - 11 BSPP | WS12BF12 | WS12BF12-SS |
| | 1⅞" - 12 ORB | WS12OF12 | --- |
| 2" | 2" - 11½ NPTF | WS16F16 | WS16F16-SS |
| | 2" - 11 BSPP | WS16BF16 | WS16BF16-SS |
| | 2½" - 12 ORB | WS16OF16 | --- |