



**Dixon® Cam & Groove Type C Coupler x Hose Shank**



356T6 aluminum



brass



316 stainless steel



unplated ductile iron

**Features:**

- finger rings are not supplied on 1" Dixon® couplings
- couplers are supplied standard with a Buna-N gasket, other gasket types are available on pages 167 - 170
- ½" Dixon® coupler has only one cam arm
- use Dixon® replacement handles only

Hose ID	356T6 Aluminum Part #	Brass Part #	316 Stainless Steel Part #	Unplated Ductile Iron Part #
1"	<b>100-C-AL</b>	<b>100-C-BR</b>	<b>100-C-SS</b>	---
1½"	<b>150-C-AL</b>	<b>150-C-BR</b>	<b>150-C-SS</b>	<b>150-C-MI</b>
2"	<b>200-C-AL</b>	<b>200-C-BR</b>	<b>200-C-SS</b>	<b>200-C-MI</b>
3"	<b>300-C-AL</b>	<b>300-C-BR</b>	<b>300-C-SS</b>	<b>300-C-MI<sup>1</sup></b>
4"	<b>400-C-AL</b>	<b>400-C-BR</b>	<b>400-C-SS</b>	<b>400-C-MI<sup>1</sup></b>
6"	<b>600-C-AL</b>	<b>600-C-BR</b>	<b>600-C-SS</b>	<b>600-C-MI<sup>1</sup></b>

<sup>1</sup> ductile iron

**Only use the crimp style shanks with the crimp style sleeves and ferrules.**  
 Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon® products.



**EZ Boss-Lock™ Cam & Groove Type C Coupler x Hose Shank**

**Feature:**

- couplers are supplied standard with a Buna-N gasket, other gasket types are available on pages 167 - 170



Size	316 Stainless Steel Part #
1"	<b>RC100EZCR</b>
1¼"	<b>RC125EZCR</b>
1½"	<b>RC150EZCR</b>
2"	<b>RC200EZCR</b>
3"	<b>RC300EZCR</b>
4"	<b>RC400EZCR</b>
6"	<b>RC600EZCR</b>

Under no circumstances should the EZ Boss-Lock™ cam arms be used on any fitting not specifically designed for their use. See page 122 for further specifications.

