NPT Threaded Bell Reducers

Features:

- other sizes available
- 304 stainless steel fittings are also available, consult Dixon® for pricing and availability

Female NPT	Female NPT	150# 316 Stain.Steel Part #	<i>3000# Forged Steel</i> Part #	<i>125# Brass</i> Part #
1⁄4"	1/8"			
3⁄8"	1/8"			
	1⁄4"	BR3825SS		
1⁄2"	1⁄4"	BR5025SS		
	³ ⁄8"	BR5038SS	BR5038FS	BR5038B ¹
3⁄4"	3⁄8"	BR7538SS		3771206C
	1⁄2"	BR7550SS	BR7550FS	BR7550B1
1"	1⁄2"	BR1050SS		BR1050B
	3⁄4"	BR1075SS	BR1075FS	BR1075B
1¼"	1"	BR1210SS		BR1210B
1½"	3⁄4"			BR1575B
	1"	BR1510SS	BR1510FS	BR1510B
	1¼"	BR1512SS	BR1512FS	
2"	1"	BR2010SS	BR2010FS	BR2010B
	1½"	BR2015SS	BR2015FS	BR2015B
21⁄2"	2"			BR2520B
3"	2"	BR3020SS		BR3020B
4"	3"			BR4030B



Κ

150# 316 stainless steel



3000# forged steel



125# brass

¹ items will be discontinued as stock is depleted

Adapters Reducer Couplings

Feature:

• ref SAE 130138

Female NPTF	Brass Previous Part # Part #		Optional Qty	Lead Free Brass ^{1, 2, 3} Part #
1⁄4" X 1⁄8"	RC2F1F	3770402C	50	
³ ⁄8" X ¹ ⁄8"	RC3F1F	3770602C	50	
³ ⁄8" X ¹ ⁄4"	RC3F2F	3770604C	50	
1⁄2" X 1⁄4"	RC4F2F	3770804C	25	
¹ /2" X ³ /8"	RC4F3F	3770806C	10	3770806CLF
³ / ₄ " X ³ / ₈ "	RC6F3F	3771206C	10	
³ ⁄ ₄ " X ¹ ⁄ ₂ "	RC6F4F	3771208C	10	3771208CLF



Κ

¹ lead free brass <=0.25% lead; Alloy CA2745; Alloy C46400

² conforms To: Safe Water Drinking Act (SWDA) of Jan. 4, 2014; California AB1953; RoHS Compliant

³ NPT threads

• For additional information on pipe dimensions please reference dixonvalve.com.