


Type A 90° Elbows  
adapter x female NPT

Cam & Groove



Features:


- maximum operating pressure: **100 PSI** (1½" - 2"); recommendations based on the use of mating Dixon® fittings at an ambient temperature of **70°F (21°C)** with standard seal installed
- for use at elevated temperatures or other unusual operating conditions, consult Dixon®
- NOT recommended for use with PTFE gaskets. NOT recommended for use with PTFE gaskets. Polypropylene cam & groove should not be mixed with metal fittings. 

| Size | Glass-Filled Polypropylene Part # | Optional Qty |
|------|-----------------------------------|--------------|
| 1½"  | <b>90PPA150</b>                   | 24           |
| 2"   | <b>90PPA200</b>                   | 24           |

Type C 90° Elbows  
coupler x hose shank



Features:


- supplied with EPDM gaskets, 304 stainless steel handles and pins
- maximum operating pressure: **100 PSI** (1½" - 2"); recommendations based on the use of mating Dixon® fittings at an ambient temperature of **70°F (21°C)** with standard seal installed
- for use at elevated temperatures or other unusual operating conditions, consult Dixon®
- NOT recommended for use with PTFE gaskets. Polypropylene cam and groove should not be mixed with metal fittings. 

| Size | Glass-Filled Polypropylene Part # | Optional Qty |
|------|-----------------------------------|--------------|
| 1½"  | <b>90PPC150</b>                   | 24           |
| 2"   | <b>90PPC200</b>                   | 24           |

Type D 90° Elbows  
coupler x female NPT



Features:


- supplied with EPDM gaskets, 304 stainless steel handles and pins
- maximum operating pressure: **100 PSI** (1½" - 2"); recommendations based on the use of mating Dixon® fittings at an ambient temperature of **70°F (21°C)** with standard seal installed
- for use at elevated temperatures or other unusual operating conditions, consult Dixon®
- NOT recommended for use with PTFE gaskets. Polypropylene cam and groove should not be mixed with metal fittings. 

| Size | Glass-Filled Polypropylene Part # | Optional Qty |
|------|-----------------------------------|--------------|
| 1½"  | <b>90PPD150</b>                   | 24           |
| 2"   | <b>90PPD200</b>                   | 24           |

Type F 90° Elbows  
adapter x male NPT



Features:

- maximum operating pressure: **100 PSI** (1½" - 2"); recommendations based on the use of mating Dixon® fittings at an ambient temperature of **70°F (21°C)** with standard seal installed
- for use at elevated temperatures or other unusual operating conditions, consult Dixon®
- NOT recommended for use with PTFE gaskets. Polypropylene cam & groove should not be mixed with metal fittings. 

| Size | Glass-Filled Polypropylene Part # | Optional Qty |
|------|-----------------------------------|--------------|
| 1½"  | <b>90PPF150</b>                   | 24           |
| 2"   | <b>90PPF200</b>                   | 24           |