

## King Crimp™ Style Ferrules

Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon® products.



Hose ID	Hose OD		Work. Pressure (PSI)		Ferrule ID	Ferrule Wall Thickness	Ferrule Overall Length	Carbon Steel Part #	304 Stainless Steel Part #
	From	To	cam & groove <sup>1</sup>	King Crimp nipple <sup>2</sup>					
1"	1-13/64"	1-16/64"	*	*	1.313"	.062"	2-13/16"	<b>CF100-1CS</b>	<b>CF100-1SS</b>
	1-17/64"	1-20/64"	*	*	1.375"	.062"	2-13/16"	<b>CF100-2CS</b>	<b>CF100-2SS</b>
	1-21/64"	1-24/64"	*	*	1.438"	.062"	2-13/16"	<b>CF100-3CS</b>	<b>CF100-3SS</b>
	1-25/64"	1-28/64"	*	*	1.500"	.062"	2-13/16"	<b>CF100-4CS</b>	<b>CF100-4SS</b>
	1-29/64"	1-32/64"	*	*	1.563"	.062"	2-13/16"	<b>CF100-5CS</b>	<b>CF100-5SS</b>
	1-33/64"	1-36/64"	*	*	1.625"	.062"	2-13/16"	<b>CF100-6CS</b>	<b>CF100-6SS</b>
	1-37/64"	1-40/64"	*	*	1.688"	.062"	2-13/16"	<b>CF100-7CS</b>	<b>CF100-7SS</b>
	1-41/64"	1-44/64"	*	*	1.750"	.062"	2-13/16"	<b>CF100-8CS</b>	<b>CF100-8SS</b>
	1-45/64"	1-48/64"	*	*	1.813"	.062"	2-13/16"	<b>CF100-9CS</b>	<b>CF100-9SS</b>
	1-49/64"	1-52/64"	*	*	1.875"	.062"	2-13/16"	<b>CF100-10CS</b>	<b>CF100-10SS</b>
1 1/4"	1-41/64"	1-44/64"	250	350	1.750"	.060"	2-13/16"	<b>CF125-3CS</b>	<b>CF125-3SS</b>
	1-45/64"	1-48/64"	250	350	1.813"	.060"	2-13/16"	<b>CF125-4CS</b>	<b>CF125-4SS</b>
	1-49/64"	1-52/64"	250	350	1.875"	.060"	2-13/16"	<b>CF125-5CS</b>	<b>CF125-5SS</b>
	1-53/64"	1-56/64"	250	350	1.938"	.060"	2-13/16"	<b>CF125-6CS</b>	<b>CF125-6SS</b>
	1-41/64"	1-44/64"	250	350	1.750"	.062"	2-13/16"	<b>CF150-1CS</b>	<b>CF150-1SS</b>
1 1/2"	1-45/64"	1-48/64"	250	350	1.813"	.062"	2-13/16"	<b>CF150-2CS</b>	<b>CF150-2SS</b>
	1-49/64"	1-52/64"	250	350	1.875"	.062"	2-13/16"	<b>CF150-3CS</b>	<b>CF150-3SS</b>
	1-53/64"	1-56/64"	250	350	1.938"	.062"	2-13/16"	<b>CF150-4CS</b>	<b>CF150-4SS</b>
	1-57/64"	1-60/64"	250	350	2.000"	.062"	2-13/16"	<b>CF150-5CS</b>	<b>CF150-5SS</b>
	1-61/64"	2"	250	350	2.063"	.062"	2-13/16"	<b>CF150-6CS</b>	<b>CF150-6SS</b>
	2-1/64"	2-4/64"	250	350	2.125"	.062"	2-13/16"	<b>CF150-7CS</b>	<b>CF150-7SS</b>
	2-5/64"	2-8/64"	250	350	2.188"	.062"	2-13/16"	<b>CF150-8CS</b>	<b>CF150-8SS</b>
	2-9/64"	2-12/64"	250	350	2.250"	.062"	2-13/16"	<b>CF150-9CS</b>	<b>CF150-9SS</b>
	2-13/64"	2-16/64"	250	350	2.313"	.062"	2-13/16"	<b>CF150-10CS</b>	<b>CF150-10SS</b>
	2-17/64"	2-20/64"	250	350	2.375"	.062"	2-13/16"	<b>CF150-11CS</b>	<b>CF150-11SS</b>
	2-21/64"	2-24/64"	250	350	2.438"	.062"	2-13/16"	<b>CF150-12CS</b>	<b>CF150-12SS</b>
	2"	2-13/64"	2-16/64"	250	300	2.313"	.062"	3-1/8"	<b>CF200-1CS</b>
2-17/64"		2-20/64"	250	300	2.375"	.062"	3-1/8"	<b>CF200-2CS</b>	<b>CF200-2SS</b>
2-21/64"		2-24/64"	250	300	2.438"	.062"	3-1/8"	<b>CF200-3CS</b>	<b>CF200-3SS</b>
2-25/64"		2-28/64"	250	300	2.500"	.062"	3-1/8"	<b>CF200-4CS</b>	<b>CF200-4SS</b>
2-29/64"		2-32/64"	250	300	2.563"	.062"	3-1/8"	<b>CF200-5CS</b>	<b>CF200-5SS</b>
2-33/64"		2-36/64"	250	300	2.625"	.062"	3-1/8"	<b>CF200-6CS</b>	<b>CF200-6SS</b>
2-37/64"		2-40/64"	250	300	2.688"	.062"	3-1/8"	<b>CF200-7CS</b>	<b>CF200-7SS</b>
2-41/64"		2-44/64"	250	300	2.750"	.062"	3-1/8"	<b>CF200-8CS</b>	<b>CF200-8SS</b>
2-45/64"		2-48/64"	250	300	2.813"	.062"	3-1/8"	<b>CF200-9CS</b>	<b>CF200-9SS</b>
2-49/64"		2-52/64"	250	300	2.875"	.062"	3-1/8"	<b>CF200-10CS</b>	<b>CF200-10SS</b>
2-53/64"		2-56/64"	250	300	2.938"	.062"	3-1/8"	<b>CF200-11CS</b>	<b>CF200-11SS</b>
2-57/64"		2-60/64"	250	300	3.000"	.062"	3-1/8"	<b>CF200-12CS</b>	<b>CF200-12SS</b>

\* consult Dixon® at [engineering@dixonvalve.com](mailto:engineering@dixonvalve.com) for pressure rating

<sup>1</sup> based on using crimp cam & groove shanks

<sup>2</sup> based on using King™ crimp nipples