



# Table of Contents

Pressure Washer Fittings .....	3 - 7
Garden Hose Fittings .....	8 - 13
Pneumatic Fittings .....	14 - 20
Maintenance and Repair .....	21 - 25

---

## Featured Products



**Turbo Nozzles**  
pg. 5



**5 Part DF Series Kit**  
pg. 17



**Special Edition Pink Constant Flow Nozzles**  
pg. 11

# Pressure Washer Display

The pressure washer display offers a wide variety of nozzles for different types of angles and sprays. This display is easily customizable and provides space for additional pressure washing products.



**PART #: PW-RETAILKIT**

**Features:**

- Retail packaging
- Retail display signage
- Posters
- Barcodes

Note: Shelving is not included.

“The packaging and organized Dixon display helped sell products we had in stock but rarely sold. Customers like how easy it is to grab the packages right off the rack.”

- Scott, New Hampshire

# Pressure Washer Fittings

## E-Series Hydraulic Couplings

### Features:

- Couplers have no internal valves, which provides maximum flow with minimum pressure drop
- Nitrile (Buna-N) seals are standard, providing a temperature range of **-40°F to 250°F** (-40°C to 121°C)
- Contact Dixon® for additional seal material options.
- Contact Dixon® for pressure ratings and other technical information.
- Interchanges with Parker ST, Hannifin SST/BST, Foster FST, Hansen ST, and Tomco ST couplings
- *Do not disconnect with pressure in line.*



### Straight Through Female Threaded Couplers



Body Size	Threads	Required Case Qty	Brass Part #
1/4"	1/4" - 18 NPTF	20	<b>PW-2EF2-B</b>
3/8"	3/8" - 18 NPTF	20	<b>PW-3EF3-B</b>

### Straight Through Male Threaded Couplers



Body Size	Threads	Required Case Qty	Brass Part #
1/4"	1/4" - 18 NPTF	20	<b>PW-2EM2-B</b>
3/8"	3/8" - 18 NPTF	20	<b>PW-3EM3-B</b>

### Straight Through Female Threaded Plugs



steel



brass

Body Size	Threads	Required Case Qty	Steel Part #	Brass Part #
1/4"	1/4" - 18 NPTF	20	---	<b>PW-E2F2-B</b>
3/8"	3/8" - 18 NPTF	20	<b>PW-E3F3</b>	<b>PW-E3F3-B</b>

### Straight Through Male Threaded Plugs



steel



brass

Body Size	Threads	Required Case Qty	Steel Part #	Brass Part #
1/4"	1/4" - 18 NPTF	20	---	<b>PW-E2M2-B</b>
3/8"	3/8" - 18 NPTF	20	<b>PW-E3M3</b>	<b>PW-E3M3-B</b>

## Pressure Washer Display Blue Bins

### Feature:

- To be used with above E-Series hydraulic couplings



Description	Required Case Qty	Part #
1 bin - 11" x 8" x 7"	1	<b>PW-BLU-BINS</b>
10 bins - 7½" x 4" x 3"	1	

# Pressure Washer Fittings

## Swiveling Quick Couplings

### Features:

- Working pressure: **3650 PSI**
- **7.8 GPM**
- Maximum temperature: **300°F (149°C)**
- For use with **AL456** only

Description	Required Case Qty	Part #
1/4" female x 22 mm x 1.5 mm swivel	4	<b>PW-AL450</b>
3/8" female x 22 mm x 1.5 mm swivel	4	<b>PW-AL453</b>



PW-AL450



PW-AL453

## Fixed Quick Coupling Plugs

### Features:

- Working pressure: **3650 PSI**
- **7.8 GPM**
- Maximum temperature: **300°F (149°C)**
- For use with **AL453** and **AL9** only

Description	Required Case Qty	Part #
1/4" female x 22 mm x 1.5 mm male	4	<b>PW-AL454</b>
3/8" female x 22 mm x 1.5 mm male	4	<b>PW-AL456</b>



PW-AL454



PW-AL456

## Quick Connect Spray Nozzles

Description	Required Case Qty	Part #
1/4" straight through plug inlet, 0° spray angle, size #4, red	4	<b>PW-MSP400</b>
1/4" straight through plug inlet, 15° spray angle, size #4, yellow	4	<b>PW-MSP415</b>
1/4" straight through plug inlet, 25° spray angle, size #4, green	4	<b>PW-MSP425</b>
1/4" straight through plug inlet, 40° spray angle, size #4, white	4	<b>PW-MSP440</b>



## Multi-Pack Quick Connect Nozzles

Description	Nozzles Included	Required Case Qty	Part #
1/4", 65° spray angle, size #40	NZ6540QCS	4	<b>PW-MSP4PAK</b>
1/4", 15° spray angle, size #4, yellow	MSP415		
1/4", 25° spray angle, size #4, green	MSP425		
1/4", 40° spray angle, size #4, white	MSP440		



### Features:

- 15° spray angle
- Maximum temperature: **195°F (91°C)**
- Ceramic orifice

## Turbo Nozzles

Nozzle Size	Description	Orifice	Maximum Working PSI	Required Case Qty	Part #
4.0	1/4" female inlet, dk. green	1.30 mm	<b>3625</b>	2	<b>PW-AL-TPR25-30</b>
5.5 - 6.0	1/4" female inlet, purple	1.50 mm	<b>3625</b>	2	<b>PW-AL-TPR25-50</b>



PW-AL-TPR25-30



PW-AL-TPR25-50

# Pressure Washer Fittings

## High Pressure Spray Nozzles



Description	Required Case Qty	Part #
1/4" male inlet, 40° spray angle, size #40	4	<b>PW-NZ4040S</b>
1/4" male inlet, 80° spray angle, size #40	4	<b>PW-NZ8040S</b>
1/4" male NPT inlet, 15° spray angle, size 4	4	<b>PW-NZ1504</b>
1/4" male NPT inlet, 25° spray angle, size 4	4	<b>PW-NZ2504</b>
1/4" male NPT inlet, 40° spray angle, size 4	4	<b>PW-NZ4004</b>

## Pressure Spray Gun



### Features:

- 3/8" female inlet
- 1/4" female outlet
- Temperatures to: **300°F (149°C)**
- Anti-fatigue pressure compensating design

Maximum PSI	GPM	Required Case Qty	Part #
<b>5075</b>	<b>12.0</b>	<b>4</b>	<b>PW-HPSG</b>

## Pressure Spray Gun



PW-AL323XX



PW-AL324XX

### Features:

- For use with **HPSG, HPSGC, HPSGHD** and **HPSGW**
- Maximum operating pressure: **5000 PSI**
- Temperature: **300°F (149°C)**
- **10.5 GPM** maximum

Length	Description	Required Case Qty	Zinc Part #
24"	1/4" male inlet x 1/4" male outlet	4	<b>PW-AL323XX</b>
36"	1/4" male inlet x 1/4" male outlet, 4" space from the end	4	<b>PW-AL324XX</b>

# Pressure Washer Fittings

## Poster



Description	Required Case Qty	Part #
pressure washer accessories poster	1	<b>PW-POSTER</b>

## Sign Holder



Description	Required Case Qty	Part #
end cap sign holder	2	<b>SIGNHOLDER</b>

## End Cap Sign



Description	Required Case Qty	Part #
pressure washer accessories end cap sign	1	<b>PW-SIGN</b>

## Shelf Graphic



Description	Required Case Qty	Part #
Dixon® shelf graphic	2	<b>SHELFGRAPHIC</b>

Boost your impulse buying traffic!

# Garden Hose Fittings

The garden hose fittings display offers a range of adapters and connectors, along with two styles of hoses. This display reminds your customers of their garden hose-related needs: demanding industrial clean up or at-home projects.



**PART #: GHD-RETAILKIT**

**Features:**

- Retail packaging
- Retail display signage
- Posters
- Barcodes

Note: Shelving is not included.

"Great point-of-sale tool for our 'will call' area."

-Tripp, Texas

To capitalize on high demand, place your display:

- By the front counter where customers may wait in line
- Next to other Dixon items as a unique seasonal display
- In related product sections as a visual anchor to draw customers' attention



# Garden Hose Fittings

## GHT Ball Valve

### Features:

- Forged brass
- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**

Required Case Qty	Brass Part #
6	<b>GHD-500GHV</b>



## Quick Connect

### Features:

- Easy push-pull ring for long lasting and quick hose attachments
- Maximum operating pressure: **150 PSI** at ambient temperature **70°F (21°C)**
- Maximum temperature **140°F (60°C)**

Description	Required Case Qty	Kit Contains Part #	Brass Part #
complete assembly	6	500QCF (2) 500QCM	<b>GHD-500QCK</b>



## Short Shank Fittings

### Features:

- Extended male GHT - deeper thread
- Complete coupling set is shipped unassembled

Hose Size	Required Case Qty	Brass Part #
3/4"	6	<b>GHD-589121K</b>



## Menders

Hose Size	Required Case Qty	Kit Contains Part #	Brass Part #
3/4"	6	1781212C (2)	<b>GHD-1781212C</b>



## Sweeper Nozzle

Thread Size	Discharge	Length	Required Case Qty	Brass Part #
3/4" GHT	3/16"	2"	6	<b>GHD-PSN76</b>



## Adjust-A-Power Nozzle

### Features:

- Ideal for patio, auto and boat, driveway and garden
- Produces 50% more power than twist nozzles
- Does not require a washer
- Leave nozzle in the open position when not in use
- Brass construction with stainless steel bearings
- Maximum operating pressure: **100 PSI** (water only) at ambient temperature **70°F (21°C)**

Thread Size	Required Case Qty	Brass Part #
3/4" GHT	6	<b>GHD-AAPN75GHT</b>



# Garden Hose Fittings



## Twist Nozzle

### Feature:

- Maximum operating pressure **150 PSI** (water only)

Thread Size	Length	Required Case Qty	Extruded Brass Part #
3/4" GHT	4"	6	<b>GHD-500AN4</b>



## Insulated Water Nozzles

### Features:

- Clip locks to any spray pattern
- Industrial strength nylon handle
- Rubber handle guard
- GHT thread on head
- Heavy duty brass valve and adjusting nut
- For use with hot water up to **140°F (60°C)**

Thread Size	Required Case Qty	Chrome Plated Zinc Part #
3/4" GHT	4	<b>GHD-SN75</b>



## Washers

### Filter Washer

Description	Kit Contains Part #	Required Case Qty	FDA black 70a duro PVC Part #
304 stainless steel mesh, FDA black 70a duro PVC	5911212F (4)	6	<b>GHD-5911212F</b>



### Black SBR Washer

ID	OD	duro	Kit Contains Part #	Required Case Qty	Part #
0.63"	1.00"	80	5911212W (4)	100	<b>GHD-5911212W</b>



## Female GHT Adapter

Female x Female	Required Case Qty	Brass Part #
3/4" x 3/4"	6	<b>GHD-5061212C</b>



## Hydrant Adapters - Pin Lug

Female Thread	Male Thread	Required Case Qty	Cast Brass Part #
1 1/2"	3/4"	4	<b>GHD-HA2576</b>
2 1/2"	3/4"	4	<b>GHD-HA1576</b>

# Garden Hose Fittings

## Y Coupler

### Features:

- Maximum working pressure: **150 PSI**
- Maximum temperature: **195°F (90.5°C)**

Required Case Qty	Zinc Plated Brass Part #
6	<b>GHD-500YC</b>



### Features:

## Y Valve

- Forged brass
- Double Y valve, swivel inlet - with Higbie cut threads (capped) to prevent cross threading
- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**

Required Case Qty	Forged Brass Part #
6	<b>GHD-500GHY</b>



## Plain Hose Nozzles

### Features:

- Finish: satin
- Maximum operating pressure: **100 PSI** (water only) at **70°F (21°C)**

Size	Thread	Overall Length	Orifice	Required Case Qty	Brass Part #
3/4"	GHT	6"	1/4"	6	<b>GHD-BN6</b>



## GHT 4-Valve Manifold

### Features:

- Forged brass body, stainless steel balls, PTFE seals
- Swivel inlet
- Maximum temperature: **120°F (49°C)**
- Maximum operating pressure: **100 PSI**

Required Case Qty	Part #
4	<b>GHD-500GH4VBK</b>



## Constant Flow Nozzle Displays

### Features:

- Shatterproof and UV resistant polycarbonate withstands tough environmental conditions
- Seals used for true water shut off
- Easy twist spray pattern adjustment
- Sold in case quantity only (30 per case), with display

Thread	45° Spray GPM @ 100 PSI	Color	Required Case Qty	Part #
3/4" GHT	25.1	clear	1	<b>GHD-CNB75GHT-GD</b>
3/4" GHT	25.1	pink	1	<b>BCA75GHT-GD</b>



Displays are easy to assemble!

# Garden Hose Fittings

## Worm Gear Clamps



### Features:

- Clamp meets SAEJ1508 which supersedes Mil Spec WW-C-440B
- Four-piece construction
- Screw design: 5/16" slotted hex head
- Maximum recommended torque 50 in. lbs.
- **All clamps sold 10 per box**

### Materials:


- Band and housing: SAE 300 series stainless
- Screw: SAE 300 series stainless

Band Width	Hose OD		Kit Contains Part #	Required Case Qty	Part #
	from	to			
1/2"	1/2"	29/32"	HSS8 (10)	4	<b>GHD-HSS8</b>
	11/16"	1-1/14"	HSS12 (10)	4	<b>GHD-HSS12</b>

## Clamp Rack

### Features:

- Top load metal rack made of nickel plated steel rods with enameled steel sign
- Sign identifies each clamp size and diameter range
- Rack with clamps contains 9 clamp sizes with diameter ranges from 7/32" to 2-3/4"
- **CRWC**, Clamps included are: 30 of part# MH4, 30 of part# MH6, 20 of part# HS10, 20 of part# HS12, 20 of part# HS20, 20 of part# HS24, 20 of part# HS28, 20 of part# HS32, 20 of part# HS36



Description	Required Case Qty	Part #
with 200 clamps	1	<b>CRWC</b>

## Rubber Vinyl Garden Hose

### Features:

- Extra tough, five-ply construction
- Exclusive, soft textured, abrasion-resistant green cover
- Dual reinforced, heavy-duty, flexible, kink-resistance
- Combines durability of rubber and easy handling of vinyl
- SEAL-TITE® leakproof coupling
- Working pressure: **400 PSI**
- Temperature range: **0°F to 140°F (-18°C to 60°C)**



Size	Required Case Qty	Rubber Vinyl Part #
5/8" x 50'	2	<b>GHD-SGH50</b>

## Contractors EPDM Water Hose

### Features:

- Heavy duty, crush proof solid brass couplings with wrench grips
- Spiral synthetic cord reinforcement
- Black cover
- Working pressure: **150 PSI**
- Temperature range: **-20°F to 180°F (-29°C to 82°C)**



Size	Required Case Qty	EPDM Part #
3/4" x 50'	2	<b>GHD-CWH50</b>

# Garden Hose Fittings

## Poster



Description	Required Case Qty	Part #
garden hose fittings poster	1	<b>GHD-POSTER</b>

## Sign Holder



Description	Required Case Qty	Part #
end cap sign holder	2	<b>SIGNHOLDER</b>

## End Cap Sign



Description	Required Case Qty	Part #
garden hose fittings end cap sign	1	<b>GHD-SIGN</b>

## Shelf Graphic



Description	Required Case Qty	Part #
Dixon® shelf graphic	2	<b>SHELFGRAPHIC</b>

How do Dixon retail displays help you sell more?

1. Make it visible
2. Make it appealing
3. Make it easy

# Pneumatic Fittings

The pneumatic fittings display offers several parts from FRLs to quick disconnects, while keeping a single product focus. This display gives your customers the flexibility to choose which fittings work best with their pneumatic systems.



**PART #: PND-RETAILKIT**

**Features:**

- Retail packaging
- Retail display signage
- Posters
- Barcodes

Note: Shelving is not included.

“After I set the Dixon display up, I realized it was helping me sell other products. When I put them all together, I saw a huge jump in sales. I’ve never seen FRLs sell so quickly.”

- Paul, Massachusetts

# Pneumatic Fittings

## B07 Carded Miniature Filter/Regulator

### Features:

- Pressure range: **5-100 PSI**
- Relieving type
- 5 micron element
- 1 oz. reservoir
- Push to lock adjusting knob
- Inlet pressure: **150 PSI** maximum
- Maximum temperature: **125°F (52°C)**
- Supplied with a GC620 gauge
- Bowl guard not available
- Transparent bowl



Port Size	Flow (SCFM)	Required Case Qty	Automatic Drain Part #	Manual Drain Part #
1/4"	14	4	<b>PND-B07-202AGC</b>	<b>PND-B07-202MGC</b>

## F07 Carded Miniature Filter

### Features:

- 5 micron element
- 1 oz. reservoir
- Inlet pressure: **150 PSI** maximum
- Maximum temperature: **125°F (52°C)**
- Transparent bowl



Port Size	Flow (SCFM)	Required Case Qty	Automatic Drain Part #	Manual Drain Part #
1/4"	24	4	<b>PND-F07-200AC</b>	<b>PND-F07-200MC</b>

## R07 Carded Miniature Regulator

### Features:

- Pressure range: **5-100 PSI**
- Relieving type
- Inlet pressure: **250 PSI** maximum
- Maximum temperature: **150°F (66°C)**
- Supplied with a GC620 gauge



Port Size	Flow (SCFM)	Required Case Qty	With Gauge Part #
1/4"	15	4	<b>PND-R07-200GRC</b>

## L07 Carded Miniature Lubricator

### Features:

- 1 oz. reservoir
- Inlet pressure: **150 PSI** maximum
- Maximum temperature: **125°F (52°C)**



Port Size	Flow (SCFM)	Required Case Qty	With Transparent Bowl Part #
1/4"	15	4	<b>PND-L07-200AC</b>

SCFM ratings given at **100 PSIG** inlet pressure for regulators, **90 PSIG** for all others.



FRLs are designed for air service only, unless otherwise indicated.

# Pneumatic Fittings



## Heavy Duty Tire Pressure Gauge

**Features:**

- 12" hose with swivel dual foot chuck inflator
- Tapered chuck nut fits wheel cover holes on cars and light trucks
- Calibrated in **2 PSI** increments from **10 to 120 PSI**

Required Case Qty	Part #
3	<b>PND-D101</b>



## Tire Inflator Chuck

**Features:**

- Ball foot chuck
- For direct connection to live air only
- Features a built-in shutoff valve (will not work on inflator gauges)
- 1/4" NPT female thread
- Maximum pressure: **150 PSI**

Required Case Qty	Brass Part #
6	<b>PND-D104</b>



## Dual Foot Tire Pressure Gauge

**Features:**

- Heavy duty hang-up ring
- Calibrated in **2 PSI** increments from **10 to 150 PSI**

Required Case Qty	Part #
6	<b>PND-DFG2</b>



## Professional Tire Pressure Gauge

**Features:**

- Permanently lubricated
- Easy to read, dual calibrated (PSI and kPa), four-sided nylon indicator bar
- Body is made of chrome-plated brass; head is chrome-plated zinc
- Pocket clip
- Calibrated in **1 PSI** increments from **5 to 45 PSI**

Required Case Qty	Part #
6	<b>PND-DFG5</b>



## Male NPTF x Hose Barb

Hose ID	Male NPTF	Required Case Qty	Kit Contains Part #	Brass Part #
3/8"	1/4"	6	1020604C (4)	<b>PND-1020604C</b>



# Pneumatic Fittings

## 5 Part Kit DF Series Industrial 1/4" Body x 1/4" Thread

Body Size	Threads	Required Case Qty	Kit Contains Part #	Part #
1/4"	1/4" - 18 NPTF	6	D2F2 2FF2-B D2M2 (3)	<b>PND-DQCKIT1</b>
1/4"	1/4" - 18 NPTF	6	D2F2 2DF2-B D2M2 (3)	<b>PND-DQCKIT2</b>



## 2 Part Kit M Series ARO 1/4" Body x 1/4" Thread

Body Size	Threads	Required Case Qty	Kit Contains Part #	Part #
1/4"	1/4" - 18 NPT	6	2MF2-B M2M2	<b>PND-DQCKIT3</b>



## 2 Part Kit J Series Automotive 1/4" Body x 1/4" Thread

Body Size	Threads	Required Case Qty	Kit Contains Part #	Part #
1/4"	1/4" - 18 NPT	6	2JF2-B J2M2	<b>PND-DQCKIT4</b>



## 2 Part Kit DF Series Industrial 1/4" Body x 1/4" Thread

Body Size	Threads	Required Case Qty	Kit Contains Part #	Part #
1/4"	1/4" - 18 NPTF	6	D2M2 (3) 2FF2-B	<b>PND-DQCKIT5</b>



## 2 Part Kit DF Series Industrial 1/4" Body x 1/4" Thread

Body Size	Threads	Required Case Qty	Kit Contains Part #	Part #
1/4"	1/4" - 18 NPTF	6	2FM2-B D2F2	<b>PND-DQCKIT6</b>



# Pneumatic Fittings

## Non-Safety Rubber Tip Blow Gun



The rubber tip will not scratch or mar delicate surfaces. The conical rubber tip can also be used to create a seal between the blow gun and fluid lines (or any other opening). The base of the tip is nickel-plated brass for additional corrosion resistance. *Must be used on air lines having a maximum regulated pressure of 30 PSI in order to comply with OSHA Standard 1910.242 (B). Safety glasses or shield must be worn when using any blow gun.*



### Features:

- Chrome plated zinc die cast body, nickel plated steel lever, vinyl thumb grip, stainless steel spring, brass valve, Buna-N seals, and rubber tip with a nickel plated brass base provide superior corrosion resistance

Required Case Qty	Part #
6	<b>PND-D201</b>

## Air Chief Safety Blow Gun



The air chief safety blow gun is designed to conform to OSHA Standard 1910.242 (B) permitting a maximum of 30 PSI outlet pressure when dead ended based on a maximum of **150 PSI** inlet pressure, as well as OSHA Standard 1910.95 regulating occupational noise level exposure. *Safety glasses or shield must be worn when using any blow gun.*



### Features:

- Recessed internal slotted screw allows easy access to valve assembly for repairs or replacement
- Chrome plated zinc die cast body, nickel-plated steel lever, vinyl thumb grip, stainless steel spring, brass valve, Buna-N seals, and nickel plated brass tip combine for superior corrosion resistance

Required Case Qty	Part #
6	<b>PND-D204-30</b>

## 3 in 1 Manifold



### Features:

- Supplies three air-operated tools from a single hose permitting use of air by more than one mechanic
- Can be mounted to a pipe at workbench or overhead
- Different tools in the shop use different styles of couplers; mount 3 different style couplers on one manifold

NPT Inlet (1)	NPT Outlets (3)	Required Case Qty	Aluminum Part #
3/8"	1/4"	6	<b>PND-D3406</b>

## Pinch-On Clamp Service Kit



### Features:

- Plastic kit box contains zinc plated 2-ear clamps: 15 of part #0709, 15 of part #0811, 15 of part #1113, 15 of part #1315, 15 of part #1518, 12 of part #1720, 12 of part #2023, 12 of part #2225, 12 of part #2327 and 1 pair of standard jaw pincers, part# 1098

Required Case Qty	Part #
2	<b>PND-SK1098</b>

# Pneumatic Fittings

## ABS Standard Dry Gauge Kit-Retail Package



Description	Kit Contains Part #	Required Case Qty	Part #
dry gauge center back mount	GC230 (4)	1	<b>PND-GAUGEKIT1</b>
dry gauge lower mount	GL130 (7)		

## Polyurethane Air Hose

(fittings included)

### Features:

- Durable and lightweight
- Nylon-reinforced braid allows for higher working pressure
- Excellent flexibility
- Oil resistant
- Durometer: Shore A 85
- Temperature range: **-40°F to 155°F (-40°C to 68°C)**
- Working pressure: **210 PSI at 70°F (21°C)**



Hose ID	Length	Male NPT	Required Case Qty	Polyurethane Part #
1/4"	50'	1/4"	3	<b>PND-450-4S</b>

## Coil-Chief Self-Storing Air Hose

(fittings included)

### Features:

- Supplied with swivel on one end
- Nylon construction



Hose ID	Length	Male NPT	Working Pressure @ 70°F (21°C)	Required Case Qty	Nylon Part #
1/4"	12'	1/4"	<b>185</b>	3	<b>PND-CC1412</b>

## Polyurethane Self-Storing Air Hose

(fittings included)

### Features:

- Extremely flexible; resists kinking
- Impervious to abrasions, heat, and oil
- Superior elasticity and coil memory
- Both ends swivel



Hose ID	Length	Male NPT	Working Pressure (PSI)	Required Case Qty	Polyurethane Part #
1/4"	25'	1/4"	<b>145</b>	3	<b>PND-PU1425</b>

# Pneumatic Fittings

## Air Tool Lubricants



### Application:


- High-grade lubricant prolongs the service life of air tools, cylinders, and accessories

### Features:

- #10 weight lubricant
- Compound is superior in performance to ordinary lubricants
- Prohibits rust and removes moisture as it lubricates
- Non-corrosive, non-reactive, and does not decompose
- Easy pour spout helps prevent costly spills

Size	Required Case Qty	Part #
1 pint	4	<b>PND-DATL016</b>
1 gallon	2	<b>PND-DATL128</b>

## Poster



Description	Required Case Qty	Part #
pneumatic fittings poster	1	<b>PND-POSTER</b>

## Sign Holder



Description	Required Case Qty	Part #
end cap sign holder	2	<b>SIGNHOLDER</b>

## End Cap Sign



Description	Required Case Qty	Part #
pneumatic fittings end cap sign	1	<b>PND-SIGN</b>

## Shelf Graphic



Description	Required Case Qty	Part #
Dixon® shelf graphic	2	<b>SHELFGRAPHIC</b>

# Maintenance & Repair

## PVC Tubing and Hose Cutters

**Features:**

- Rugged construction cuts up to 3/4" tubing or hose
- Corrosion resistant hardened steel blade ensures straight, crisp cuts for optimum fit

---

Part #
<b>TC97</b>
<b>TC97RB</b>

---



**Features:**

- Cuts low-pressure fabric reinforced hose up to 1" OD
- Reversible blade

---

Part #
<b>HC90</b>
<b>HC90RB (replacement blade)</b>

---



**Features:**

- Cuts hose and tubing up to 1 1/8" OD
- Tough fiberglass reinforced handle
- Stainless steel blade

---

Part #
<b>LHC95</b>
<b>LHC95RB (replacement blade)</b>

---




Catch customers at the point of purchase!

# Maintenance & Repair

## American Made PTFE Tape (Purple)

### Features:

- Thickness: 3.5 mil (0.0035 mm)
- Temperature range: **-450°F to 500°F (-268°C to 260°C)**
- Superior quality
- *Not for use in oxygen applications* 




Size	Length	Part #
1/2"	520"	<b>TTPM50-520</b>
	700"	<b>TTPM50-700</b>
	1429"	<b>TTPM50-1429</b>
3/4"	520"	<b>TTPM75-520</b>
	700"	<b>TTPM75-700</b>
	1429"	<b>TTPM75-1429</b>
1"	520"	<b>TTPM100-520</b>
	700"	<b>TTPM100-700</b>
	1429"	<b>TTPM100-1429</b>

## Industrial PTFE Tape (White)

### Features:

- Thickness: 3.5 mil (0.0035 mm)
- Temperature range: **-212°F to 500°F (-136°C to 260°C)**



Size	Length	Part #	Optional Qty
1/2"	260"	<b>TTA50</b>	550
	520"	<b>TTB50</b>	500
	1296"	<b>TTC50</b>	250
3/4"	260"	<b>TTA75</b>	350
	520"	<b>TTB75</b>	350
1"	520"	<b>TTB100</b>	250

## Stainless Steel PTFE Tape (Gray)

### Features:

- Thickness: 4 mil
- Temperature range: **-450°F to 550°F (-268°C to 288°C)**
- Useful on stainless steel threaded joints or connections
- PTFE with nickel added, nickel acts like a ball bearing
- Made in the US



Size	Length	Part #	Optional Qty
1/2"	260"	<b>TTA50SS</b>	10

## Industrial Heavy Duty PTFE Tape (Pink)

### Features:

- Thickness: 4 mil
- Temperature range: **-400°F to 500°F (-240°C to 260°C)**




Size	Length	Part #	Optional Qty
1/2"	540"	<b>TTBP50</b>	500

## PTFE Tape for LP Gas (Yellow)

### Features:

- Thickness: 4 mil
- Maximum temperature: **500°F (260°C)**
- Underwriters Listed



Size	Length	Part #	Optional Qty
1/2"	260"	<b>TTA50LP</b>	500

# Maintenance & Repair

## Thread Sealant Paste

### Features:

- Temperature range: **-300°F to 500°F (-184°C to 260°C)**
- *Do not use with oxygen*



Size	Part #	Optional Qty
¼ pint	<b>LCTS14</b>	24
½ pint	<b>LCTS1</b>	24
1 pint	<b>LCTS2</b>	12
1 quart	<b>LCTS3</b>	12



## Joint Sealant Gasket Material

### Features:

- GORE-TEX® interchangeable
- Form-In-Place expanded PTFE gasket material with adhesive backing
- Manufactured from 100% virgin PTFE
- Unaffected by all common chemicals (pH from 0-14)
- Unlimited shelf life
- Resilient with low cold flow
- Requires less force than standard gasket materials
- Pressure range: **vacuum to 3000 PSI**
- Temperature range: **-450°F to 600°F (-268°C to 316°C)**
- Made in the USA
- FDA compliant #21CFR177.1550
- Larger spools are available; contact Dixon® for price and availability

Size	Length	Part #
¼"	20'	<b>LCJS4-20</b>
¼"	50'	<b>LCJS4-50</b>
⅜"	25'	<b>LCJS6-25</b>
½"	15'	<b>LCJS8-15</b>
¾"	15'	<b>LCJS12-15</b>



## Leak Detector

### Features:

- Detects leaks by forming bubbles which remain for up to ten minutes
- Will not cause corrosion or deterioration
- Color: fluorescent yellow
- Non-toxic, non-freezing
- Temperature range: **-7°F to 180°F (-20°C to 82°C)**
- Meets federal specification MIL-L-25567-C

Size	Part #	Case Qty
8 oz.	<b>LCLD</b>	24



# Maintenance & Repair

## Dixon® Coupling Lubricant

### Application:

- For use in assembly operations involving natural or synthetic rubber or plastic; also an excellent lubricant when rubber or plastic needs to be cut, machined, pressed, turned, trimmed, or ground



### Features:


- Biodegradable lubricant for coupling shanks, O-rings, hoses, sleeves, rubber washers, and grommets
- Once coupling lubricant dries, slipping action goes away

Size	Part #
1 liter	<b>DCL20</b>
4 liters	<b>DCL80</b>

## WD-40 Smart Straw



### Features:

- Permanently attached straw
- Flip up for precision spray; flip down for regular spray action
- Sold in case quantities only
- *Should not be used as a lubricant for coupling shanks* 

Size	Part #	Case Qty
11 oz.	<b>WD40</b>	12

## Spill Kits



oil spill kit



universal spill kit

### Features:

- Easily stored behind a seat or in a storage compartment allowing drivers to act quickly when responding to a spill
- Poly-zip bag and bucket kits feature:
  - 10 pads (15" x 19")
  - 3 socks (3" x 4')
  - 2 disposal bags with ties
  - 1 pair nitrile gloves

Description	Part #
oil only, in 6½ gallon pail	<b>DSK5-O</b>
universal, in 6½ gallon pail	<b>DSK5-U</b>
oil only, in clear poly bag with zipper	<b>DSKB-O</b>
universal, in clear poly bag with zipper	<b>DSKB-U</b>



# Maintenance & Repair

## Rapp-it Pipe Repair Kit

### Applications:

- On-site emergency pipe repair in varied industrial applications: mining, processing, oil and gas, petrochemical, manufacturing, marine, and agricultural industries for use with steel, poly, pvc, copper, concrete, or rubber

### Sizes:

- 2" x 12', 3" x 12', 4" x 12', 4" x 16', 4" x 30'

### Features:

- No mixing or measuring required, easy to apply
- Quickly contains leaking substances, keeping a workplace safe
- Tenacious bond: 5 to 10 min., functional cure: approx. 30 min.
- One product that can be used on a vast array of pipe sizes, shapes, and materials
- Suitable for use on acid lines, gas, most diluted chemicals, sea water, fuels, and oil
- Chemical resistance: resistant to hydrocarbons, ketones, esters, alcohols, halocarbons, aqueous salt solutions, dilute acids/bases
- Suitable for wet or dry pipe: apply under fresh and saltwater

### Materials:

- Bandage: woven fiberglass
- Resin: water-activated polyurethane resin

### Specifications:

- Pressure resistance up to **360 PSI (2500kPA)**
- Shore D hardness at full cure (24 hours): 80 durometer
- Lap shear tensile strength on steel (1" x 1" x 1/16"): 400kg (6.2MPa)
- Compressive strength: **8,000 PSI (55 MPa)**
- Temperatures:
  - Continuous **-40°F to 250°F (-40° to 121°C)**
  - Intermittent **-40°F to 300°F (-40° to 149°C)**
  - Heat resistance: **300°F (150°C)**

### Approvals:

- NATO Certification 4730-66-1257893
- NSF 61 compliant for potable water



Size	Description	Part Number
2" x 12'		<b>RAP122</b>
3" x 12'	kit includes woven fiberglass bandage infused with water-activated resin and a 90 mm stick of Rapp-it Steel Putty	<b>RAP123</b>
4" x 12'		<b>RAP124</b>
4" x 16'		<b>RAP164</b>
4" x 30'		<b>RAP304</b>





Dixon®, founded in 1916, is a premier manufacturer and supplier of hose couplings, valves, dry-disconnects, swivels, and other fluid transfer and control products. The company's global reach includes a wide range of products for numerous industries including petroleum exploration, refining, transportation, chemical processing, food & beverage, steel, fire protection, construction, mining, and manufacturing. Dixon®'s strategic objective is to create solutions that make products safer, leak-free, longer lasting, and always available.

[dixonvalve.com](http://dixonvalve.com) • *Customer Service:* 877.963.4966



*The Right Connection®*

**Dixon®**

800 High Street, Chestertown, MD 21620  
Fax: 800.283.4966

