

**Dixon® Sanitary Style****Features: Crimp Ferrules**

- AISI 304 stainless steel
- ferrules have a surface finish of 63 or better



Size	Hose OD		304 Stainless Steel Part #
	From	To	
1"	1-26/64"	1-28/64"	<b>F16G-1453</b>
	1-29/64"	1-31/64"	<b>F16G-1500</b>
	1-32/64"	1-34/64"	<b>F16G-1547</b>
	1-35/64"	1-37/64"	<b>F16G-1594</b>
	1-38/64"	1-40/64"	<b>F16G-1641</b>
1½"	1-58/64"	1-61/64"	<b>F24G-1969</b>
	1-62/64"	2-1/64"	<b>F24G-2031</b>
	2-2/64"	2-5/64"	<b>F24G-2094</b>
	2-6/64"	2-9/64"	<b>F24G-2156</b>
	2-10/64"	2-13/64"	<b>F24G-2219</b>
	2-14/64"	2-17/64"	<b>F24G-2281</b>
	2-18/64"	2-21/64"	<b>F24G-2344</b>
2"	2-30/64"	2-33/64"	<b>F32G-2531</b>
	2-34/64"	2-37/64"	<b>F32G-2594</b>
	2-38/64"	2-41/64"	<b>F32G-2656</b>
	2-42/64"	2-45/64"	<b>F32G-2719</b>
	2-52/64"	2-55/64"	<b>F32G-2875</b>
	2-56/64"	2-59/64"	<b>F32G-2938</b>
2½"	3"	3-3/64"	<b>F40G-3063</b>
	3-4/64"	3-7/64"	<b>F40G-3125</b>
	3-8/64"	3-11/64"	<b>F40G-3188</b>
	3-12/64"	3-15/64"	<b>F40G-3250</b>
	3-16/64"	3-19/64"	<b>F40G-3313</b>
	3-20/64"	3-23/64"	<b>F40G-3375</b>
3"	3-36/64"	3-39/64"	<b>F48G-3625</b>
	3-40/64"	3-43/64"	<b>F48G-3688</b>
	3-44/64"	3-47/64"	<b>F48G-3750</b>
	3-48/64"	3-51/64"	<b>F48G-3813</b>
	3-52/64"	3-55/64"	<b>F48G-3875</b>
	3-56/64"	3-59/64"	<b>F48G-3938</b>
4"	3-61/64"	4"	<b>F48G-4016</b>
	4-40/64"	4-43/64"	<b>F64G-4688</b>
	4-44/64"	4-47/64"	<b>F64G-4750</b>
	4-48/64"	4-51/64"	<b>F64G-4813</b>
	4-52/64"	4-55/64"	<b>F64G-4875</b>
	4-56/64"	4-59/64"	<b>F64G-4938</b>
	5-5/64"	5-8/64"	<b>F64G-5141</b>

**Holedall™ DIN External****Crimp Female Stems**

Size	DIN	316 Stainless Steel Part #
1½"	40	<b>HA0240</b>
2"	50	<b>HA0241</b>
2½"	65	<b>HA0242</b>
3"	80	<b>HA0243</b>

**Male Stems**

Size	DIN	316 Stainless Steel Part #
1½"	40	<b>HA0235</b>
2"	50	<b>HA0236</b>
2½"	65	<b>HA0237</b>
3"	80	<b>HA0238</b>

- please visit [dixonvalve.com](http://dixonvalve.com) for crimp recommendations