



Gauges & Thermometers

Designed for long, reliable service under rugged conditions

Dry Gauges

Applications:

- pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement

Sizes:

- 1½", 2", 2½", 3½", 4½" (*contractor pressure gauge only*)

Materials:

- ABS
- brass
- stainless steel

Features:

- standard dry and liquid-filled pressure gauges, compound pressure gauges, vacuum gauges and welding gauges
- lower and center back mount type
- designed for long, reliable service under rugged conditions

Specifications:

- contact Dixon® for accuracy, temperature range, connectivity, specifications and approvals for each style



Standard



Stainless Steel Standard



Brass Standard



Process



Flutterguard™



Stainless Panel



Contractor Pressure



Compound



Vacuum



General Purpose Digital



Welding

Liquid Filled Gauges

Applications:

- designed for severe service applications, providing the corrosion resistance and durability of a permanently sealed gauge

Sizes:

- face size: 2½", 4"

Materials:

- ABS
- brass
- stainless steel

Feature:

- lower and center back mounts



Stainless Case



Stainless Steel



All Stainless Steel



ABS



Brass

Thermometers & Miscellaneous

thermometers

- bi-metal
- model 30
- model 31
- model 50
- model 52
- pocket
- magnetic surface mount
- threaded thermowells
- 180° steam gauge siphon



Bi-metal



Magnetic



Pocket Bi-metal



180° steam gauge siphon



threaded thermowells

- Dixon™ couplings and retention devices are designed to work safely for their intended use. The selection of the proper hose, coupling and retention device, and the proper application of the coupling to the hose are of utmost importance.

- Users must consider the size, temperature, application, media, pressure and hose and coupling manufacturer's recommendations when selecting the proper hose assembly components. Dixon™ recommends that all hose assemblies be tested in accordance with the Association for Rubber Products Manufacturer's (ARPM) recommendations and be inspected regularly (before each use) to ensure that they are not damaged or have become loose. Visit ARPMINC.com for more information.

- Where safety devices are integral to the coupling, they must be working and utilized. The use of supplementary safety devices such as safety clips or safety cables are recommended.

- If any problem is detected, couplings must be removed from service immediately.

- Dixon™ is available to consult, train and recommend the proper selection and application of all fittings we sell. We strongly recommend that distributors and end users make use of Dixon Testing and Recommendation Services. Call 877.963.4966 or click dixonvalve.com to learn more.

Dixon®

800 High Street • Chestertown, MD 21620
 ph: 877.963.4966 • fx: 410-778-4702 • 800-283-4966
dixonvalve.com



© 2017 DVCC

GAUGE&THERMOM0917inhouse

