

### Hose Shank Hose Swivels

**Application:**

- for use with petroleum and home heating oil hose

**Feature:**

- prevents hose twisting or kinking



Male NPT	Shank Size	Bronze Part #
1½"	1½"	<b>1565U</b>
<b>repair kit</b>		
Description		Part #
replacement seal kit and retaining ring		<b>1500SK</b>

### Heavy Duty Hose Swivels

**Features:**

- male NPT x female NPT threaded connections
- heavy duty internal thrust bearing and anti-friction seal design ensures swiveling at **-40°F (-40°C)**
- can be lubricated without disassembly by using the optional grease nipple kit below



Male NPT	Female NPT	Bayloy Part #
1¼"	1¼"	<b>SWMF125</b>
1½"	1½"	<b>SWMF150</b>
2"	2"	<b>SWMF200</b>
<b>repair kits</b>		
Description		Part #
inlet swivel grease nipple kit (optional)		<b>SWMF-RK1</b>
inlet swivel seal and wear kit		<b>SWMF-RK22</b>
complete inlet swivel rebuild kit		<b>SWMF-RK32</b>
2" FNPT replacement inlet swivel		<b>SWMF-RK42</b>
1½" FNPT replacement inlet swivel		<b>SWMF-RK52</b>

### MannTek Hose Swivels

**Features:**

- allows the hose to relax to it's natural rest position while allowing freedom of movement without adding torque stress at the point of connection
- simple design, low maintenance - consists of 2 body halves, ball bearings and a washer
- male NPT x female NPT threaded connections
- FKM seals standard, Chemraz® and Kalrez® optional contact Dixon®
- working pressure: **150 PSI**
- maximum temperature: **300°F (149°C)**



Size	316 Stainless Steel Part #	Aluminum Part #
¾"	<b>HS075SS</b>	<b>HS075AL</b>
1"	<b>HS100SS</b>	<b>HS100AL</b>
1½"	<b>HS150SS</b>	<b>HS150AL</b>
2"	<b>HS200SS</b>	<b>HS200AL</b>
3"	<b>HS300SS</b>	<b>HS300AL</b>
4"	<b>HS400SS</b>	<b>HS400AL</b>