



DRIVEN BY POSSIBILITY™

GATES® PRO™ SERIES:

CR1 HYDRAULIC HOSE

HYDRAULIC SOLUTIONS FOR THE FACTORY AND FIELD.

**STRONG, RELIABLE AND FLEXIBLE.
ENGINEERED TO DELIVER DEPENDABLE,
APPLICATION-SPECIFIC PERFORMANCE.**

Gates PRO™ Series CR1 variable pressure hydraulic hoses deliver performance and reliability in a one-wire construction.

Engineered for less demanding hydraulic applications, our new line of professional-grade hoses are designed to balance product performance and investment for everyday uses. All sizes deliver consistent performance to SAE and EN industry specifications.

We believe operating challenges are made to be overcome. That's why thousands of industrial facilities, global operations and OE manufacturers around the world choose Gates hose and hydraulic systems to power their demanding fluid power applications.

FEATURES + BENEFITS

- Ideal for non-severe, medium-pressure hydraulic applications with low flexure requirements
- Application-specific design offers reliable performance that gets the job done
- Meets SAE 100R1 and EN853 1SN performance standards
- Part of Gates PRO™ Series Hose Portfolio
- Manufactured to Gates high-quality professional standards



DRIVEN BY POSSIBILITY™

GATES® PRO™ SERIES CR1 HYDRAULIC HOSE:

PROFESSIONAL- GRADE HYDRAULIC HOSE SOLUTIONS

Gates® PRO™ Series CR1 variable pressure hydraulic hoses are qualified for use with the full line of PRO™ Series couplings to ensure end-to-end performance — providing a broad range of engineered solutions for targeted hydraulic applications.

Over the last 50 years, Gates has driven standard adoption in the industry. We have used our extensive knowledge of standards, industries and applications, as well as our expertise in materials science to create a competitive edge for our customers by developing application-specific solutions that offer reliable performance.



THE RIGHT PRODUCTS FOR YOUR APPLICATION

PRODUCT SPECIFICATIONS:

- **TUBE:** Black, oil resistant, synthetic rubber tube
- **REINFORCEMENT:** One layer of braided high-tensile steel
- **COVER:** Black, abrasion resistant, synthetic rubber
- **CERTIFIED:** MSHA Flame Resistant
- **TEMPERATURE RANGE:** -40°F to +212°F (-40°C to +100°C)

**GATES IS YOUR
SOURCE FOR
HYDRAULIC HOSE
+ COUPLINGS.**

ASK YOUR SALES
REPRESENTATIVE FOR
MORE INFORMATION.

DESCRIPTION	ID (INCH)	WP (PSI)	BURST (PSI)	MIN. BEND RADIUS (INCH)
4 CR1	1/4	3,275	13,100	4
5 CR1	5/16	3,125	12,500	4.5
6 CR1	3/8	2,600	10,400	5
8 CR1	1/2	2,325	9,300	7
10 CR1	5/8	1,900	7,600	8
12 CR1	3/4	1,525	6,100	9.5
16 CR1	1	1,250	5,000	11.8

INDUSTRIES + APPLICATIONS:

- Agriculture
- Construction
- Mining
- Manufacturing
- Return Lines
- Low Flex Accessory Lines
- Auxiliary Lines
- Drain Lines

GATES.COM

GLOBAL | 14MAR2019