



Marine Hose

4684CF
(Wet Exhaust-Corrugated)
(Specification 4684CF)

Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard	Stock (X) or Minimum	Gates	List Price
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack	Order Qty.	Item No.	Per Ft.
1	25.4	1.44	36.6	100	.69	25.0	635	3.0	76	.51	.23	10 ft.	X	4684-1540	\$13.20
1-1/8	28.6	1.56	39.6	100	.69	25.0	635	4.0	102	.56	.25	10 ft.	X	4684-1545	14.29
1-1/4	31.8	1.69	42.9	100	.69	25.0	635	4.0	102	.61	.28	10 ft.	X	4684-1551	15.07
1-3/8	34.9	1.81	46.0	85	.59	25.0	635	4.0	102	.66	.30	10 ft.	X	4684-1556	15.50
1-1/2	38.1	1.94	49.3	85	.59	25.0	635	4.0	102	.70	.32	10 ft.	X	4684-1561	15.81
1-5/8	41.3	2.06	52.3	75	.52	20.0	508	5.0	127	.75	.34	10 ft.	X	4684-1601	16.01
1-3/4	44.5	2.19	55.6	75	.52	20.0	508	5.0	127	.80	.36	10 ft.	X	4684-1611	16.94
1-7/8	47.6	2.31	58.7	60	.41	20.0	508	5.0	127	.83	.38	10 ft.	X	4684-1651	17.93
2	50.8	2.44	62.0	60	.41	20.0	508	5.0	127	.88	.40	10 ft.	X	4684-1660	18.71
2-1/8	54.0	2.56	65.0	55	.38	20.0	508	6.0	152	.93	.42	10 ft.	X	4684-1670	19.40
2-1/4	57.2	2.69	68.3	55	.38	20.0	508	6.0	152	.98	.45	10 ft.	X	4684-1680	20.40
2-3/8	60.3	2.81	71.4	50	.34	20.0	508	7.0	178	1.03	.47	10 ft.	X	4684-1690	21.94
2-1/2	63.5	2.94	74.7	50	.34	20.0	508	7.0	178	1.08	.49	10 ft.	X	4684-1700	22.56
2-5/8	66.7	3.06	77.7	40	.28	15.0	381	9.0	229	1.12	.51	10 ft.	X	4684-1711	22.86
2-3/4	69.9	3.19	81.0	40	.28	15.0	381	10.0	254	1.17	.53	10 ft.	X	4684-1720	23.05
2-7/8	73.0	3.31	84.1	40	.28	15.0	381	11.0	279	1.21	.55	10 ft.	X	4684-1730	23.83
3	76.2	3.44	87.4	40	.28	15.0	381	12.0	305	1.26	.57	10 ft.	X	4684-1740	24.38
3-1/2	88.9	4.06	103.1	35	.24	15.0	381	17.0	432	1.45	.66	10 ft.	X	4684-1750	27.63
4	101.6	4.44	112.8	30	.21	10.0	254	24.0	610	1.64	.74	10 ft.	X	4684-1760	29.16
4-1/2	114.3	4.94	125.5	25	.17	5.0	127	27.0	914	1.84	.84	10 ft.	200 ft.	4684-1764	31.75
5	127.0	5.44	138.2	15	.10	5.0	127	30.0	1016	2.03	.92	10 ft.	200 ft.	4684-1766	34.34
6	152.4	6.46	164.1	15	.10	5.0	127	36.0	—	2.42	1.10	10 ft.	200 ft.	4684-1722	39.51

RECOMMENDED FOR: Marine wet exhaust and general purpose applications. Suitable for coolant lines where tight bends are required.

TEMPERATURE: -40°F to +212°F (-40°C to +100°C) continuous service.

CONSTRUCTION: **Tube:** Type C (Nitrile). Black. Oil and heat resistant.
Reinforcement: Synthetic fabric with built-in wire.
Cover: Type A (Neoprene). Black with red spiral stripe. Oil and heat resistant.

HOSE ENDS: Plain End. Straight or Enlarged Ends on special order.

PACKAGING: 1", 1-1/4", 1-3/8", 1-1/2", 1-5/8", 1-7/8": Packaged 50' coiled in a carton.
4-1/2" through 6": Packaged in straight lengths in woven fiber.
All other sizes: Packaged 10' per carton.

BRANDING: Continuous transfer label every 10 ft. Example: "Gates 4684CF Engine Coolant-Marine Wet Exhaust 2 Inch Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 200 feet per size. Lengths can be as short as one foot, but minimum billing is for ten feet.
For enlarged or straight ends, contact Denver Industrial Hose Marketing for pricing.

REMNANT LENGTHS: None.

STANDARDS: Meets requirements of SAE J20R2, SAE J20R5, SAE J2006.
Tube: RMA (Class B) Medium oil resistance.
Cover: RMA (Class C) Limited oil resistance.