



™

**Kuriyama of America, Inc.**

360 E. State Parkway  
Schaumburg, IL 60173-5335 USA


**Phone:** (847) 755-0360

**Toll-Free FAX:** (800) 800-0320

**International FAX:** (847) 885-0996 **Email:** [sales@kuriyama.com](mailto:sales@kuriyama.com)

## Item # K6158-08X300, Kuri Tec® K6158 Series 0.750 in. Nominal OD High-Purity Non-Toxic PVC Potable Water Hose

A High Purity Non-Conductive NSF Certified, Phthalate Free Hose with Colored Jacket which is Ideal for Potable water and Deionized water transfer



[Construction](#) | [Features](#) | [Applications](#) | [Service Temperature Range](#) | [Nominal Specifications](#) | [Specifications](#) | [Compliance Footnotes](#)

### Construction

-

**Tube**

Clear Phthalate Free PVC compound, formulated in compliance with FDA and NSF criteria

**Reinforcement**

High Tensile Strength Yarn

**Cover**

Phthalate Free PVC compound, available in solid color: K6158 - Grey. Additional non-toxic colors (Red, Black, Blue, Green, Yellow and Purple) are available on a special order basis.

### Features

-

- Made with Phthalate Free PVC compounds certified under

**Features**

NSF-51/NSF-61.

- White or gray jacket to reduce tendency for algae growth and U. V. degradation in warm sunny applications.
- Non-marking cover.
- Non-perforated cover.
- Non-conductive compounds.
- Silicone-free.
- One-piece lengths.
- RoHS compliant.
- Now Phthalate Free!

**Applications****Application**

- Transfer of Portable Water.
- Transfer of Deionized Water.
- Induction Welding Tubing lines.
- Temporary Residential Water Supply Lines.
- Water Transfer Lines for Semiconductor Manufacturing, where applicable.
- Applications requiring a Non-Conductive hose.

**Service Temperature Range****Service Temperature [Min]**25 °F  
-4 °C**Service Temperature [Max]**150 °F  
65 °C**Nominal Specifications****Size Code**

08

**Nominal ID**1/2 in  
12.7 mm**Nominal OD**0.750 in  
19.1 mm

	19.1 mm
<b>Max. Working Pressure at 70°F (20°C)</b>	200 psi
<b>Max. Working Pressure at 122°F (50°C)</b>	100 psi
<b>Standard Length</b>	300 ft
<b>Approx. Wt. per Pkg.</b>	40 lb

## Specifications

<b>Brand</b>	Kuri Tec®
<b>Series</b>	K6158
<b>Type</b>	Potable Water Hose
<b>Style</b>	High Purity Non-Conductive PVC Potable Water Hose
<b>Color</b>	Grey
<b>Packaging</b>	Coils
<b>Body Material</b>	Phthalate Free PVC Compound

## Compliance Footnotes

**Compliance Footnotes**

- **FDA** - The PVC ingredients used are sanctioned for food contact use under CFR title 21, parts 170-199 or FD&C Act, section 409(h), notifications relating to food contact substance.
- **NSF** - The inner core tube PVC material is certified under NSF/ANSI standard 51: Food Equipment Materials and is also certified as Potable Water Material under NSF/ANSI Standard 61: Drinking Water System Components - Health Effects for end use not to exceed a maximum of 128.9 square inches per liter. NSF - This hose is certified under NSF/ANSI standard 51: Food Equipment Materials.
- **Phthalate Free** - Manufactured from all phthalate free

materials

- **RoHS** - The product complies with the requirements of the EU directive 2002/95/EC which is on the restriction of the use of certain hazardous substances in electrical and electronic equipment.