



General Properties of 60 Durometer Skirtboard Rubber

- Excellent abrasion-resistance.
- Excellent weather-resistance



SPECIFICATIONS:

Blended SBR/NR slit sheet, Plate Finish:

Style **SK60**: 60 Duro hardness (Shore Durometer A)

Polymer: Styrene-Butadiene and Isoprene Rubber, Natural

PACKAGING: 50 Ft. Rolls

Color: Black

Common Name: Skirtboard Rubber

ISO/ASTM Designation: SBR/NR

Style	ASTM Specification (SI units)	Temp. Range	Durometer	Tensile Strength (psi)	Elongation (%)	Finish
SK60	D 2000 M1AA 608	-22°F to +158°F	55 – 65	1050	300%	Plate

ORDERING INFORMATION:

Part Number	Gauge x Width (in)	Avg. Length (Linear Ft/Roll)	Approx. Lbs/Roll
SK60-08x3x50	1/4 x 3	50	23
SK60-08x4x50	1/4 x 4	50	30
SK60-08x5x50	1/4 x 5	50	38
SK60-08x6x50	1/4 x 6	50	45
SK60-08x8x50	1/4 x 8	50	61
SK60-08x10x50	1/4 x 10	50	76
SK60-08x12x50	1/4 x 12	50	91
SK60-12x3x50	3/8 x 3	50	34
SK60-12x4x50	3/8 x 4	50	45
SK60-12x5x50	3/8 x 5	50	57
SK60-12x6x50	3/8 x 6	50	68
SK60-12x8x50	3/8 x 8	50	91
SK60-12x10x50	3/8 x 10	50	114
SK60-12x12x50	3/8 x 12	50	136
SK60-16x3x50	1/2 x 3	50	45
SK60-16x4x50	1/2 x 4	50	61
SK60-16x5x50	1/2 x 5	50	76
SK60-16x6x50	1/2 x 6	50	91
SK60-16x8x50	1/2 x 8	50	121
SK60-16x10x50	1/2 x 10	50	151
SK60-16x12x50	1/2 x 12	50	182
SK60-24x3x50	3/4 x 3	50	68
SK60-24x6x50	3/4 x 6	50	136
SK60-24x8x50	3/4 x 8	50	182
SK60-24x9x50	3/4 x 9	50	205
SK60-24x10x50	3/4 x 10	50	227
SK60-24x12x50	3/4 x 12	50	273
SK60-32x3x50	1 x 3	50	91
SK60-32x6x50	1 x 6	50	182
SK60-32x8x50	1 x 8	50	242
SK60-32x10x50	1 x 10	50	303
SK60-32x12x50	1 x 12	50	363