



## SPECIFICATIONS: SBR - Plate Finish

**PACKAGING: 50 Ft. Rolls**

Style **SESK**: 65 Duro hardness (Shore A)

Style	ASTM Specification (SI units)	Temp. Range	Durometer	Tensile Strength (psi)	Elongation (%)	Finish
SESK60	D 2000 M1AA 654	-22°F to +158°F	60 – 70	610	300%	Plate

## ORDERING INFORMATION:

Part Number	Gauge x Width (in)	Avg. Length (Linear ft/Roll)	Approx. lbs/Roll
SESK60-08x3x50	1/4 x 3	50	21
SESK60-08x4x50	1/4 x 4	50	28
SESK60-08x6x50	1/4 x 6	50	43
SESK60-08x8x50	1/4 x 8	50	57
SESK60-08x10x50	1/4 x 10	50	71
SESK60-08x12x50	1/4 x 12	50	85
SESK60-12x2x50	3/8 x 2	50	21
SESK60-12x3x50	3/8 x 3	50	32
SESK60-12x4x50	3/8 x 4	50	42
SESK60-12x6x50	3/8 x 6	50	63
SESK60-12x8x50	3/8 x 8	50	84
SESK60-12x10x50	3/8 x 10	50	105
SESK60-12x12x50	3/8 x 12	50	127
SESK60-16x3x50	1/2 x 3	50	42
SESK60-16x4x50	1/2 x 4	50	56
SESK60-16x5x50	1/2 x 5	50	71
SESK60-16x6x50	1/2 x 6	50	85
SESK60-16x8x50	1/2 x 8	50	113
SESK60-16x10x50	1/2 x 10	50	141
SESK60-16x12x50	1/2 x 12	50	169
SESK60-24x3x50	3/4 x 3	50	63
SESK60-24x4x50	3/4 x 4	50	85
SESK60-24x6x50	3/4 x 6	50	127
SESK60-24x8x50	3/4 x 8	50	165
SESK60-24x10x50	3/4 x 10	50	211
SESK60-24x12x50	3/4 x 12	50	253
SESK60-32x3x50	1 x 3	50	85
SESK60-32x4x50	1 x 4	50	113
SESK60-32x6x50	1 x 6	50	169
SESK60-32x8x50	1 x 8	50	226
SESK60-32x10x50	1 x 10	50	282
SESK60-32x12x50	1 x 12	50	339
SESK60-48x10x50	1 1/2 x 10	50	455

